



*Mark IV
Mark V
Sliding
Glass Doors*



Mark IV & Mark V Sliding Glass Doors

- Mark IV Doors are glazed with single tempered glass for safety
- Mark V Doors feature 5/8" insulated tempered glass for safety and energy saving thermal efficiency
- All-aluminum construction provides beauty, durability and practicality
- Full 5-5/8" frame depth provides a heavy, strong construction
- Flush mounted recessed pulls with simple up/down latch eliminate accidental lockout
- Plated steel ball bearing wheel provides a smooth open/close action
- Adjustable wheel carriage for effortless operation of sliding vents
- Aluminum track provides an easy glide
- Sloped-sill with weep/drainage holes provides for easy water run off
- Double fin seal weather-strip at jambs and interlock helps block air and water infiltration
- Vinyl coated wool pile weather stripping on top and bottom rail helps prevent air and water infiltration
- Tubular door stiles provide clean architectural style with maximum strength
- Heavy-duty full screen is standard, allowing ventilation while protecting against insect infiltration
- Frame finish available in Bronze or White
- Mark IV and Mark V are available in 80" and 96" heights
- Optional grids are available with the Mark V Sliding Glass Door
- Optional tinted, turtle and Low-E Glass is available

3600 Port Jacksonville Parkway ■ Jacksonville, FL 32226

Manufacturer reserves the right to substitute components as necessary for continued product improvement.